



# Material Safety Data Sheet

MSDS ID NO.: 0137SPE012  
Revision date: 01/30/2004

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

**Product name:** SSA E85  
**Synonyms:** SSA ED75/ED85; E-75; E75; E-85; E85; Ethanol/Gasoline Fuel Blend; Fuel Ethanol ED75/ED85  
**Chemical Family:** Gasoline/Ethanol  
**Formula:** Mixture

**Supplier:**  
Speedway/Superamerica LLC  
P O BOX 1500  
ENON OH 45501

**Other information:** 419-421-3070  
**Emergency telephone number:** 877-627-5463

## 2. COMPOSITION/INFORMATION ON INGREDIENTS

E85 is a mixture of ethyl alcohol and gasoline that is approved for use in an automobile spark ignition engine. Can contain small amounts of dye and other additives (>0.02%) which are not considered hazardous at the concentrations used.

### Product information

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
SSA E85	Mixture	100			

### Component Information

Name	CAS Number	Weight %	ACGIH Exposure Limits:	OSHA - Vacated PELs - Time Weighted Ave	Other:
Ethyl Alcohol	64-17-5	75-85	= 1000 ppm TWA	=1000 ppm TWA 1900 mg/m <sup>3</sup> TWA	
Gasoline	Mixture	15-25	=300 ppm TWA; =500 ppm STEL		
Saturated Hydrocarbons	Mixture	008.3000 - 012.0000			
Aromatic Hydrocarbons	Mixture	003.0000 - 006.0000			
Xylene	1330-20-7	000.8000 - 002.3000	= 100 ppm TWA = 150 ppm STEL	= 100 ppm TWA = 150 ppm STEL = 435 mg/m <sup>3</sup> TWA = 655 mg/m <sup>3</sup> STEL	
Toluene	108-88-3	000.5000 - 002.3000	= 50 ppm TWA skin - potential for cutaneous absorption	= 100 ppm TWA = 150 ppm STEL = 375 mg/m <sup>3</sup> TWA = 560 mg/m <sup>3</sup> STEL	
Unsaturated Hydrocarbons	Mixture	000.2000 - 002.3000			
1,2,4-Trimethylbenzene	95-63-6	000.3000 - 000.7500	= 25 ppm TWA	= 125 mg/m <sup>3</sup> TWA = 25 ppm TWA	
Benzene	71-43-2	000.1000 - 000.5000	= 0.5 ppm TWA = 2.5 ppm STEL skin - potential for cutaneous absorption	= 10 ppm TWA unless specified in 1910.1028 = 25 ppm Ceiling unless specified in 1910.1028 = 50 ppm STEL 10 min, unless specified in 1910.1028	OSHA Exposure Limit as specified in 1910.1028: =1.0 ppm TWA = 5 ppm STEL = 0.5 ppm Action Level
Ethyl Benzene	100-41-4	000.2000 - 000.5000	= 100 ppm TWA = 125 ppm STEL	= 100 ppm TWA = 125 ppm STEL = 435 mg/m <sup>3</sup> TWA = 545 mg/m <sup>3</sup> STEL	

**Notes:**

The manufacturer has voluntarily elected to reflect exposure limits contained in OSHA's 1989 air contaminants standard in its MSDS's, even though certain of those exposure limits were vacated in 1992.

### 3. HAZARDS IDENTIFICATION

#### EMERGENCY OVERVIEW

THIS PRODUCT IS A CLEAR LIQUID WITH A STRONG HYDROCARBON ODOR. IT IS A VOLATILE AND EXTREMELY FLAMMABLE LIQUID THAT MAY CAUSE FLASH FIRES. KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME. CONTAINS BENZENE WHICH MAY CAUSE CANCER OR BE TOXIC TO BLOOD-FORMING ORGANS. NEVER SIPHON THIS PRODUCT BY MOUTH. IF SWALLOWED, THIS PRODUCT MAY GET SUCKED INTO THE LUNGS (ASPIRATED) AND CAUSE LUNG DAMAGE OR EVEN DEATH.

**OSHA WARNING LABEL:**

**DANGER!**  
**EXTREMELY FLAMMABLE.**  
**ASPIRATION (INADVERTENT SUCTION) OF LIQUID INTO THE LUNGS CAN PRODUCE CHEMICAL PNEUMONIA OR EVEN DEATH.**  
**CONTAINS BENZENE WHICH MAY CAUSE CANCER OR BE TOXIC TO BLOOD-FORMING ORGANS.**

**CONSUMER WARNING LABEL:**

**GASOLINE HEALTH AND SAFETY WARNING STATEMENT:**

**EXTREMELY FLAMMABLE, VAPORS MAY EXPLODE.  
HARMFUL OR FATAL IF SWALLOWED.  
LONG TERM EXPOSURE TO VAPORS HAS CAUSED CANCER IN LABORATORY ANIMALS.  
KEEP FACE AWAY FROM NOZZLE WHILE FILLING.  
KEEP NOZZLE AWAY FROM EYES AND SKIN.  
NEVER SIPHON BY MOUTH.  
DON'T OVERFILL TANK.  
FOR USE AS A MOTOR FUEL ONLY.**

**STATIC ELECTRICITY, SPARK EXPLOSION, ELECTRONIC DEVICES WARNING:**

**DO NOT GET BACK IN YOUR VEHICLE WHILE REFUELING.  
RE-ENTRY COULD CAUSE STATIC ELECTRICITY BUILD UP.  
USE APPROVED CONTAINER.  
PUT CONTAINER ON GROUND (NEVER ON OR IN A VEHICLE).  
KEEP NOZZLE IN CONTACT WITH CONTAINER.  
KEEP CELLULAR PHONES OR OTHER DEVICES IN YOUR VEHICLE DURING REFUELING.**

**Inhalation:**

Prolonged breathing of high ethanol vapor concentrations can produce headache, dizziness, nausea, incoordination and impaired vision. Excessive overexposure can cause central nervous system depression, loss of consciousness, liver damage and death resulting from respiratory failure. Exposure to vapor concentrations of gasoline exceeding 1,000 ppm can cause respiratory irritation, headache, dizziness, nausea and loss of coordination. Higher concentrations may cause loss of consciousness, cardiac sensitization, coma and death resulting from respiratory failure. Intentional overexposure to high concentrations of product vapors (such as huffing) can cause nervous system and brain damage, convulsions and sudden death from cardiac arrest.

**Ingestion:**

Liquid ingestion can cause inebriation, headache, incoordination, gastrointestinal pain, nausea, and vomiting leading to central nervous system depression. Aspiration (inadvertent suction) of liquid into the lungs must be avoided as even small quantities in the lungs can produce chemical pneumonitis, pulmonary edema/hemorrhage and even death.

**Skin contact:**

Prolonged and repeated liquid contact can cause defatting and drying of the skin and can lead to irritation and/or dermatitis.

**Eye contact:**

Liquid may cause mild to severe irritation. Splash contact or high vapor concentrations can produce an immediate burning and stinging sensation.

**Carcinogenic Evaluation:**

**Product information**

Name	IARC:	NTP:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
SSA E85 Mixture	NE			

**Notes:**

The International Agency for Research on Cancer (IARC) has determined that there is inadequate evidence for the carcinogenicity of gasoline in humans. IARC determined that limited evidence of carcinogenicity in animals exists. IARC's overall evaluation of gasoline, in spite of limited carcinogenicity evidence, has resulted in the IARC designation of gasoline as possibly carcinogenic to humans (Group 2B) because gasoline contains benzene.

IARC has determined that there is inadequate evidence for the carcinogenicity of gasoline engine exhaust in humans or animals. However, IARC's overall evaluation on gasoline engine exhaust, in spite of the absence of carcinogenicity data, has resulted in the IARC designation of gasoline engine exhaust as possibly carcinogenic to humans (Group 2B) because of the presence of certain engine exhaust components.

The International Agency for Research on Cancer (IARC) has determined that there is sufficient evidence for the carcinogenicity of alcoholic beverages (ethanol) in humans (Group 1).

**Component Information**

Name	IARC:	NTP:	ACGIH - Carcinogens:	OSHA - Select Carcinogens:
Ethyl Alcohol 64-17-5	A2-Possible Human Carcinogen		A4 - Not Classifiable as a Human Carcinogen	
Xylene 1330-20-7			A4 - Not Classifiable as a Human Carcinogen	
Toluene 108-88-3			A4 - Not Classifiable as a Human Carcinogen	
Benzene 71-43-2	Supplement 7, 1987; Monograph 29, 1982	Known Carcinogen Reasonably Anticipated To Be A Carcinogen	A1 - Confirmed Human Carcinogen	Present
Ethyl Benzene 100-41-4	Monograph 77, 2000		A3 - Animal Carcinogen	

**Notes:**

The International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), and OSHA have determined that 1,3-butadiene is a chemical possibly carcinogenic to humans (Group 2B).

The International Agency for Research on Cancer (IARC) has concluded that ethyl benzene is possibly carcinogenic to humans (Group 2B).

## 4. FIRST AID MEASURES

**Inhalation:**

If affected, move person to fresh air. If breathing is difficult, administer oxygen. If not breathing or if no heartbeat, give artificial respiration or cardiopulmonary resuscitation (CPR). Immediately call a physician. If symptoms or irritation occur with any exposure, call a physician.

**Skin contact:**

Wash with soap and large amounts of water. Remove contaminated clothing. If symptoms or irritation occur, call a physician.

**Ingestion:**

If swallowed, do not induce vomiting and do not give liquids. Immediately call a physician.

**Eye contact:**

Flush eyes with large amounts of tepid water for at least 15 minutes. If symptoms or irritation occur, call a physician.

**Medical conditions aggravated by exposure:** Pre-existing eye, skin, respiratory, liver and/or kidney disorders may be aggravated by exposure to components of this product. Pre-existing eye, skin, respiratory disorders and impaired liver function may be aggravated by overexposure to ethanol. Persons on disulfiram (antabuse) therapy should be aware that the ethyl alcohol in the product is hazardous to them just as is alcohol from any source. Disulfiram reactions (vomiting, headache and even collapse) may follow ingestion of small amounts of alcohol.

## 5. FIRE FIGHTING MEASURES

**Suitable extinguishing media:** For small fires, Class B fire extinguishing media such as CO<sub>2</sub>, dry chemical, foam (AFFF/ATC) or water spray can be used. For large fires, water spray, fog or foam (AFFT/ATC) can be used. Fire fighting should be attempted only by those who are adequately trained and equipped with proper protective equipment.

**Specific hazards:** This product has been determined to be a flammable liquid per the OSHA Hazard Communication Standard, and should be handled accordingly. Vapors may travel along the ground or be moved by ventilation and ignited by many sources such as pilot lights, sparks, electric motors, static discharge, or other ignition sources at locations distant from material handling. Flashback can occur along vapor trail. For additional fire related information, see NFPA 30 or the North American Emergency Response Guide 128.

**Special protective equipment for firefighters:** Avoid using straight water streams. Water may be ineffective in extinguishing low flash point fires, but can be used to cool exposed surfaces. Avoid excessive water spray application. Water spray and foam (AFFF/ATC) must be applied carefully to avoid frothing and from as far a distance as possible. Keep run-off water out of sewers and water sources.

**Flash point:** -50 to 55 F  
**Autoignition temperature:** C.A. 495 F  
**Flammable limits in air - lower (%):** 1.4 (Gasoline)  
**Flammable limits in air - upper (%):** 19.0 (Ethanol)

**NFPA rating:**  
Health: 1  
Flammability: 3  
Reactivity: 0  
Other: -

**HMS classification:**  
Health: 1  
Flammability: 3  
Reactivity: 0  
Special: \*See Section 8 for guidance in selection of personal protective equipment.

## 6. ACCIDENTAL RELEASE MEASURES

**Personal precautions:** Keep public away. Isolate and evacuate area. Shut off source if safe to do so. Eliminate all ignition sources. Advise authorities and National Response Center (800-424-8802) if substance has entered a watercourse or sewer. Notify local health and pollution control agencies, if appropriate. Contain liquid with sand or soil. Recover and return free product to proper containers. Use suitable absorbent materials such as vermiculite, sand, or clay to clean up residual liquids.

## 7. HANDLING AND STORAGE

**Handling:**

Comply with all applicable EPA, OSHA, NFPA and consistent state and local requirements. Use appropriate grounding and bonding practices. Store in properly closed containers that are appropriately labeled and in a cool well-ventilated area. Do not expose to heat, open flames, strong oxidizers or other sources of ignition. Do not cut, drill, grind or weld on empty containers since they may contain explosive residues. Avoid skin contact. Exercise good personal hygiene including removal of soiled clothing and prompt washing with soap and water.

For use as a motor fuel only. Product should never be used as a solvent due to its flammable and potentially toxic properties. Siphoning by mouth can result in lung aspiration which can be harmful or fatal.

Portable containers of 12 gallons (45 liters) or less should never be filled while they are in or on a motor vehicle or marine craft. Static electric discharge can ignite fuel vapors when filling non-grounded containers or vehicles on trailers. Containers should be placed on the ground. The nozzle spout must be kept in contact with the container before and during the entire filling operation. Use only approved containers. A buildup of static electricity can occur upon re-entry into a vehicle during fueling especially in cold or dry climate conditions. The charge is generated by the action of dissimilar fabrics (i.e., clothing and upholstery) rubbing across each other as a person enters/exits the vehicle. A flash fire can result from this discharge if sufficient flammable vapors are present. Therefore, do not get back in your vehicle while refueling. Cellular phones and other electronic devices may have the potential to emit electrical charges (sparks). Sparks in potentially explosive atmospheres (including fueling areas such as gas stations) could cause an explosion if sufficient flammable vapors are present. Therefore, turn off cellular phones and other electronic devices when working in potentially explosive atmospheres or keep devices inside your vehicle during refueling.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### PERSONAL PROTECTIVE EQUIPMENT

<b>Engineering measures:</b>	Local or general exhaust required in an enclosed area or with inadequate ventilation.
<b>Respiratory protection:</b>	Approved organic vapor chemical cartridge or supplied air respirators should be worn for exposures to any components exceeding the TLV or STEL. Observe respirator protection factor criteria cited in ANSI Z88.2. Self-contained breathing apparatus should be used for fire fighting.
<b>Skin and body protection:</b>	Use nitrile rubber, viton or PVA gloves for repeated or prolonged skin exposure.
<b>Eye protection:</b>	No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields.
<b>Hygiene measures:</b>	No special protective clothing is normally required. Select protective clothing depending on industrial operations. Use mechanical ventilation equipment that is explosion-proof.

## 9. PHYSICAL AND CHEMICAL PROPERTIES:

<b>Appearance:</b>	Clear Liquid
<b>Physical state (Solid/Liquid/Gas):</b>	Liquid
<b>Substance type (Pure/Mixture):</b>	Mixture
<b>Color:</b>	Clear or Colored
<b>Odor:</b>	Hydrocarbon
<b>Molecular weight:</b>	Not determined.
<b>pH:</b>	Neutral
<b>Boiling point/range:</b>	90-437 F
<b>Melting point/range:</b>	Not determined.
<b>Decomposition temperature:</b>	Not applicable.
<b>Specific gravity:</b>	0.70-0.77
<b>Density:</b>	5.9-6.3 lbs/gal
<b>Bulk density:</b>	No data available.
<b>Vapor density:</b>	No data available.
<b>Vapor pressure:</b>	43-776 mm Hg @ 100 F
<b>Evaporation rate:</b>	No data available.

**Solubility:** Appreciable  
**Solubility in other solvents:** No data available.  
**Partition coefficient (n-octanol/water):** No data available.  
**VOC content(%):** 100%  
**Viscosity:** No data available.

## 10. STABILITY AND REACTIVITY

**Stability:** The material is stable at 70 F, 760 mm pressure.  
**Polymerization:** Will not occur.  
**Hazardous decomposition products:** Combustion produces carbon monoxide, aldehydes, aromatic and other hydrocarbons.  
**Materials to avoid:** Strong oxidizers such as nitrates, chlorates, peroxides.  
**Conditions to avoid:** Excessive heat, sources of ignition, open flame.

## 11. TOXICOLOGICAL INFORMATION

**Acute toxicity:**

### Product information

Name	CAS Number	Inhalation:	Dermal:	Oral:
SSA E85	Mixture	No data available	n/a	n/a

Lifetime inhalation studies with full vaporized gasoline (67, 292 and 2,056 ppm) produced kidney damage and kidney tumors in male rats but not in female rats or male and female mice. Female mice developed a slightly higher incidence of liver tumors compared to controls at the highest exposure level. Results from separate studies with compounds producing similar effects, i.e., 1,4-dichlorobenzene and perchloroethylene, have shown that the kidney damage and kidney tumors develop via the formation of alpha-2u-globulin, a mechanism unique to the male rat. Humans do not form alpha-2u-globulin, therefore, tumors resulting from this mechanism are not relevant in humans. The biologic significance of the mouse liver tumor response with regard to human health risk is questionable.

This product may contain ethanol or ethyl alcohol at a concentration of >0.1% Intentional abuse, misuse or other massive exposure to ethanol may result in multiple organ damage and/or death. Chronic ingestion of large amounts of ethanol can cause cancer and damage to the liver, kidney, heart, brain, nervous system and stomach. Ethyl alcohol ingestion during pregnancy can adversely affect the unborn child. Studies in laboratory animals involving prolonged and repeated exposures have resulted in such effects as embryotoxicity, immunotoxicity and teratogenicity. Mutagenic effects have been reported in both in vitro and in vivo systems but usually at high dosages.

Summary of health effect information on gasoline engine exhaust:

Combustion of gasoline produces gases and particulates which include carbon monoxide, carbon dioxide, oxides of nitrogen and/or sulfur and hydrocarbons. Significant exposure to carbon monoxide vapors decreases the oxygen carrying capacity of the blood and may cause tissue hypoxia via formation of carboxyhemoglobin. Overexposure to CO can cause headache, nausea, nervous system depression, coma and death.

Summary of Health Effect Data on ED75/ED85 Components.

This product contains benzene at a level of >0.1%. Repeated or prolonged exposure to benzene at concentrations in excess of the TLV may cause serious injury to blood-forming organs. Significant chronic exposure to benzene vapor has been reported to produce various blood disorders ranging from anemia to certain forms of leukemia (cancer) in man. Benzene produced tumors in rats and mice in lifetime chronic toxicity studies, but the response has not been consistent across species, strain, sex or route of exposure. Animal studies on benzene have demonstrated immune toxicity, chromosomal aberrations, testicular effects and alterations in reproductive cycles and embryo/fetotoxicity, but not teratogenicity.

The product contains >1.0% ethyl benzene (EB). Rats and mice exposed to 750 ppm EB for 6 hours/day, 5 days/week for two years developed kidney tumors in male and female rats and lung tumors in male mice and liver tumor in female mice.

## 12. ECOLOGICAL INFORMATION

### Ecotoxicity effects:

Product can cause fouling of shoreline and may be harmful to aquatic life in low concentrations. This product does not concentrate or accumulate in the food chain.

The aquatic toxicity of gasoline is as follows:

#### Freshwater Toxicity:

LD50 is 8 ppm at 96 hours in bluegill.  
TLM is 90 ppm at 24 hours in juvenile shad.

#### Saltwater Toxicity:

LC50 is 2 ppm at 96 hours in mullet.  
LD50 is 1.5 ppm at 96 hours in grass shrimp.  
LC50 is 2 ppm at 96 hours in menhaden.  
TLM is 91 ppm at 24 hours in juvenile shad.

## 13. DISPOSAL CONSIDERATIONS

**Cleanup Considerations:**

This product as produced is not specifically listed as an EPA RCRA hazardous waste according to federal regulations (40 CFR 261). However, when discarded or disposed of, it may meet the criteria of an "ignitable" hazardous waste (D001). This product could also contain benzene at >0.5 ppm and could exhibit the characteristics of "toxicity" (D018) as determined by the toxicity characteristic leaching procedure (TCLP). This material could become a hazardous waste if mixed or contaminated with a hazardous waste or other substance(s). It is the responsibility of the user to determine if disposal material is hazardous according to federal, state and local regulations.

**14. TRANSPORT INFORMATION****49 CFR 172.101:****DOT:**

**Transport Information:** This material when transported via US commerce would be regulated by DOT Regulations.

**Proper shipping name:** Alcohols, N.O.S.  
**UN/Identification No:** UN 1987  
**Hazard Class:** 3  
**Packing group:** II  
**DOT reportable quantity (lbs):** Not applicable.

**TDG (Canada):**

**Proper shipping name:** Alcohols, N.O.S.  
**UN/Identification No:** UN 1987  
**Hazard Class:** 3  
**Packing group:** II  
**Regulated substances:** Not applicable.

**15. REGULATORY INFORMATION****Federal Regulatory Information:**

**US TSCA Chemical Inventory Section 8(b):** This product and/or its components are listed on the TSCA Chemical Inventory.

**OSHA Hazard Communication Standard:** This product has been evaluated and determined to be hazardous as defined in OSHA's Hazard Communication Standard.

**EPA Superfund Amendment & Reauthorization Act (SARA):**

**SARA Section 302:** This product contains the following component(s) that have been listed on EPA's Extremely Hazardous Substance (EHS) List:

Name	CERCLA/SARA - Section 302 Extremely Hazardous Substances and TPQs
Ethyl Alcohol	NA
Gasoline	NA
Saturated Hydrocarbons	NA
Aromatic Hydrocarbons	NA
Xylene	NA
Toluene	NA
Unsaturated Hydrocarbons	NA
1,2,4-Trimethylbenzene	NA
Benzene	NA
Ethyl Benzene	NA

**SARA Section 304:**

This product contains the following component(s) identified either as an EHS or a CERCLA Hazardous substance which in case of a spill or release may be subject to SARA reporting requirements:

Name	CERCLA/SARA - Hazardous Substances and their Reportable Quantities
Ethyl Alcohol	NA
Gasoline	NA
Saturated Hydrocarbons	NA
Aromatic Hydrocarbons	NA
Xylene	= 100 lb final RQ = 45.4 kg final RQ
Toluene	= 0.454 kg final RQ = 1 lb final RQ = 10 lb final RQ = 100 lb final RQ = 1000 lb final RQ = 4.54 kg final RQ = 45.4 kg final RQ = 454 kg final RQ
Unsaturated Hydrocarbons	NA
1,2,4-Trimethylbenzene	NA
Benzene	= 0.454 kg final RQ = 0.454 kg statutory RQ = 1 lb final RQ = 1 lb statutory RQ = 10 lb final RQ = 10 lb final RQ receives an adjustable RQ of 10 lbs based on potential carcinogenicity in August 14, 1989 final rule = 100 lb final RQ = 4.54 kg final RQ = 4.54 kg final RQ receives an adjustable RQ of 10 lbs based on potential carcinogenicity in August 14, 1989 final rule = 45.4 kg final RQ
Ethyl Benzene	= 100 lb final RQ = 1000 lb final RQ = 45.4 kg final RQ = 454 kg final RQ

**SARA Section 311/312:**

The following EPA hazard categories apply to this product:

- Acute Health Hazard.
- Chronic Health Hazard.
- Fire Hazard.

**SARA Section 313:**

This product contains the following component(s) that may be subject to reporting on the Toxic Release Inventory (TRI) From R:

Name	CERCLA/SARA 313 Emission reporting:
Ethyl Alcohol	None
Gasoline	None
Saturated Hydrocarbons	None
Aromatic Hydrocarbons	None
Xylene	= 1.0 percent de minimis concentration
Toluene	= 1.0 percent de minimis concentration
Unsaturated Hydrocarbons	None
1,2,4-Trimethylbenzene	= 1.0 percent de minimis concentration
Benzene	= 0.1 percent de minimis concentration
Ethyl Benzene	= 0.1 percent de minimis concentration

### State and Community Right-To-Know Regulations:

The following component(s) of this material are identified on the regulatory lists below:

#### Ethyl Alcohol

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	developmental toxicity (when in alcoholic beverages); initial date 10/1/87
New Jersey Right-To-Know:	sn 0844
Pennsylvania Right-To-Know:	Present
Massachusetts Right-To Know:	Teratogen
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic, Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - third degree
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

#### Gasoline

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed

#### Saturated Hydrocarbons

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.

Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed
<b>Aromatic Hydrocarbons</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed
<b>Xylene</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 2014
Pennsylvania Right-To-Know:	environmental hazard
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic, Flammable
Michigan critical materials register list:	Annual usage threshold = 100 pounds (all isomers)
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - third degree
New Jersey - Environmental Hazardous Substances List:	SN 2014
Illinois - Toxic Air Contaminants	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	= 1 lb Land/Water RQ = 1,000 lbs Air RQ
<b>Toluene</b>	

Louisiana Right-To-Know:	Not Listed
California Proposition 65:	developmental toxicity; initial date 1/1/91
New Jersey Right-To-Know:	sn 1866
Pennsylvania Right-To-Know:	environmental hazard
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic, Flammable; skin
Michigan critical materials register list:	Annual usage threshold = 100 pounds
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - third degree
New Jersey - Environmental Hazardous Substances List:	SN 1866
Illinois - Toxic Air Contaminants	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	= 1 lb Land/Water RQ = 1,000 lbs Air RQ
<b>Unsaturated Hydrocarbons</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	Not Listed.
Pennsylvania Right-To-Know:	Not Listed.
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Not Listed
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed
New Jersey - Environmental Hazardous Substances List:	Not Listed
Illinois - Toxic Air Contaminants	Not Listed
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed
<b>1,2,4-Trimethylbenzene</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 1929 sn 2716
Pennsylvania Right-To-Know:	[present] environmental hazard
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	Not Listed

New Jersey - Environmental Hazardous Substances List:	SN 2716
Illinois - Toxic Air Contaminants	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	Not Listed
<b>Benzene</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	carcinogen; initial date 2/27/87 developmental toxicity; initial date 12/26/97 male reproductive toxicity; initial date 12/26/97 sn 0197
New Jersey Right-To-Know:	environmental hazard; special hazardous substance
Pennsylvania Right-To-Know:	Carcinogen; Extraordinarily hazardous
Massachusetts Right-To Know:	Not Listed.
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic, Flammable, Carcinogen; skin
Michigan critical materials register list:	Annual usage threshold = 100 pounds
Massachusetts Extraordinarily Hazardous Substances:	carcinogen; extraordinarily hazardous
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	[present]
New Jersey - Special Hazardous Substances:	carcinogen; flammable - third degree; mutagen
New Jersey - Environmental Hazardous Substances List:	SN 0197
Illinois - Toxic Air Contaminants	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	= 1 lb Land/Water RQ = 10 lbs Air RQ
<b>Ethyl Benzene</b>	
Louisiana Right-To-Know:	Not Listed
California Proposition 65:	Not Listed
New Jersey Right-To-Know:	sn 0851
Pennsylvania Right-To-Know:	environmental hazard
Massachusetts Right-To Know:	Present
Florida substance List:	Not Listed.
Rhode Island Right-To-Know:	Toxic, Flammable
Michigan critical materials register list:	Not Listed.
Massachusetts Extraordinarily Hazardous Substances:	Not Listed
California - Regulated Carcinogens:	Not Listed
Pennsylvania RTK - Special Hazardous Substances:	Not Listed
New Jersey - Special Hazardous Substances:	flammable - third degree
New Jersey - Environmental Hazardous Substances List:	SN 0851
Illinois - Toxic Air Contaminants	Present
New York - Reporting of Releases Part 597 - List of Hazardous Substances:	= 1 lb Land/Water RQ = 1,000 lbs Air RQ

**Canadian Regulatory Information:**

Canada DSL/NDSL Inventory: This product and/or its components are listed either on the Domestic Substances List (DSL) or the Non Domestic Substance List (NDSL).

Name	Canada - WHMIS: Classifications of Substances:	Canada - WHMIS: Ingredient Disclosure:
Ethyl Alcohol	B2; D2B	0.1% (English Item 684, French Item 805)
Xylene	B2; D2A; D2B	
Toluene	B2; D2A	1% (English Item 1578, French Item 1622)
1,2,4-Trimethylbenzene	B3	0.1% (English Item 1640, French Item 1684) 1% (English Item 1638, French Item 1682)
Benzene	B2; D2A	0.1% (English Item 153, French Item 277)
Ethyl Benzene	B2; D2A; D2B	0.1% (English Item 697, French Item 854)

## 16. OTHER INFORMATION

**Additional Information:** No data available.

**Prepared by:** Craig M. Parker Manager, Toxicology and Product Safety

The information and recommendations contained herein are based upon tests believed to be reliable. However, Speedway SuperAmerica (SSA) does not guarantee their accuracy or completeness nor shall any of this information constitute a warranty, whether expressed or implied, as to the safety of the goods, the merchantability of the goods, or the fitness of the goods for a particular purpose. Adjustment to conform to actual conditions of usage maybe required. SSA assumes no responsibility for results obtained or for incidental or consequential damages, including lost profits arising from the use of these data. No warranty against infringement of any patent, copyright or trademark is made or implied.

**End of Safety Data Sheet**